

Product Showcase



▲ Grill gauge

Grill Gauge Products LLC introduces the Original Grill Gauge, a hand-held device that monitors the amount of propane remaining in a tank. The gauge incorporates the same specifications that the propane industry uses to fill and weigh tanks – by factoring the principles of the relative weight of liquid propane and the tare weight of the tank itself. The device hooks to the top of the tank and can be read when the tank is lifted off the ground.

For more information, visit www.grillgauge.com.

Analyzer

Control Instruments' standalone Model 690 Btu Calorific Analyzer optimizes burner efficiencies through measuring and controlling blended gas mixtures. The analyzer is manufactured for monitoring the heating value and energy content of flammable solvents and combustible gases in the Btu range to measure alternate fuel supplies. It is offered for process monitoring and control and is a direct measurement of calorific value, ranging from 0 to 1,100 Btu/cubic foot. These economical, fully heated, air aspirator driven assemblies come complete and ready to install.

For more information, visit www.controlinstruments.com.

► Lubricating compound

Gasoil Chemicals introduces

Thred Gard, a lubricating compound that helps protect against troublesome seizing, galling, rust and corrosion found in many industrial and manufacturing environments. Thred Gard is non-dripping and non-hardening. It is available in three compounds for use at different high-temperature levels

and three sizes – ¼-pound, ½-pound and 1-pound brush-top containers. For more information, visit www.gasoila.com.



» **MORE PRODUCTS.** Visit us online at LPGasMagazine.com to see more featured products. If you would like to see your product featured, please contact us at lpgasmag@questex.com.

BOLO
PROFESSIONAL
Combustible Gas Leak Detector



The BOLO® professional gas leak detector is a feature-rich, value-added precision instrument designed specifically for the service or safety technician responsible for quick and accurate detection of combustible gas leaks. Sensitive to very low levels of propane, methane, butane, hydrogen. Set point for alarm is 5000 ppm. Variable tick rate frequency triggered as low as 5 to 10 ppm. Solid-state sensor, microprocessor control, dual LED visual alerts and audible alert, automatic shut-off, low battery warning. Kit comes complete with hard case, detector, earphone, batteries and soft pouch w/clip.

NOVA Systems Products, LLC
The EXPERTS in Gas Detection

TOLL FREE 866-734-0200
www.novasystemsproducts.com